SUNPOWER

MAXEON 3 SOLAR PANEL

405-420 W | Up to 22.2% Efficient

Ideal for residential applications



Black backsheet, black frame

More Lifetime Energy

Designed to maximise energy generation through leading efficiency, enhanced performance in high temperatures, and higher energy conversion in low-light conditions like mornings, evenings and cloudy days.

Uncompromising Durability

Engineered to power through all types of weather conditions with crackresistant cells and reinforced connections that protect against fatigue and corrosion, to an electrical architecture that mitigates the impact of shade and prevents hot-spot formation.



Superior Sustainability

Clean ingredients, responsible manufacturing, and lasting energy production for 40 years make SunPower Maxeon panels the most sustainable choice in solar.



The Industry's Longest Warranty

SunPower Maxeon panels are covered by a 40-year warranty¹ backed by extensive third-party testing and field data from more than 33 million panels deployed worldwide.

Product and power coverage Year 1 minimum warranted output Maximum annual degradation

40 Years 98.0% 0.25%



Learn more about the SPR-MAX3-XXX-BLK-R sunpower.maxeon.com

MAXEON 3 POWER: 405-420 W | EFFICIENCY: Up to 22.2%

Electrical Data					
	SPR-MAX3- 420-BLK-R	SPR-MAX3- 415-BLK-R	SPR-MAX3- 410-BLK-R	SPR-MAX3- 405-BLK-R	
Nominal Power (Pnom) ²	420 W	415 W	410 W	405 W	
Power Tolerance	+5/0%	+5/0%	+5/0%	+5/0%	
Panel Efficiency	22.2%	21.9%	21.6%	21.4%	
Rated Voltage (Vmpp)	35.5 V	35.3 V	35.1 V	34.9 V	
Rated Current (Impp)	11.82 A	11.75 A	11.68 A	11.61 A	
Open-Circuit Voltage (Voc) (+/-3)	40.7 V	40.7 V	40.7 V	40.7 V	
Short-Circuit Current (Isc) (+/-3)	12.65 A	12.64 A	12.63 A	12.62 A	
Max. System Voltage	1000 V IEC				
Maximum Series Fuse	25 A				
Power Temp Coef.	-0.27% / °C				
Voltage Temp Coef.	–0.236% / °C				
Current Temp Coef.	0.058% / °C				

Certifications and Compliance

social fairness. 5

SVHC-163

TUV

IEC 61215, IEC 61730

ISO 9001:2015, ISO 14001:2015

First solar panel labeled for ingredient

water stewardship, material reutilization,

First solar panel line certified for material health,

renewable energy & carbon management, and


Panels can contribute additional points toward

RoHS, ISO 45001:2018, Recycle Scheme, REACH

transparency and LBC-compliance.⁴

LEED and BREEAM certifications.

Operating Condition And Mechanical Data		
Temperature	-40°C to +85°C	
Impact Resistance	25 mm diameter hail at 23 m/s	
Solar Cells	112 Monocrystalline Maxeon Gen 3	
Front Glass	High-transmission tempered glass with anti- reflective coating	
Junction Box	IP-68, Stäubli (MC4), 2 bypass diodes	
Weight	21.2 kg	
Max. Load ⁶	Wind: 2400 Pa, 244 kg/m² front & back Snow: 5400 Pa, 550 kg/m² front	
Frame	Class 1 black anodized (highest AAMA rating)	



FRAME PROFILE



(A) Cable Length: 1225 mm +/-10 mm
(B) Long Side: 32 mm
Short Side: 24 mm



Please read the safety and installation instructions. Visit www.sunpower.maxeon.com/int/PVInstallGuideIEC. Paper version can be requested through techsupport.ROW@maxeon.com.

1 40-year warranty is not available in all countries or all installations and requires registration, otherwise our 25-year warranty applies. Service availability varies by country and installation provider.

2 Standard Test Conditions (1000 W/m² irradiance, AM 1.5, 25° C). NREL calibration Standard: SOMS current, LACCS FF and Voltage.

3 Class C fire rating per IEC 61730.

4 Maxeon DC panels first received the International Living Future Institute Declare Label in 2016.

5 Maxeon DC panels are Cradle to Cradle Certified ${}^{\rm M}$ Silver $\,$ -

www.c2ccertified.org/certified-products-and-materials/maxeon-solar-panels. Cradle to Cradle Certified™ is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.

6 As per IEC 61215-2016 tested and certified.

Made in Philippines (Cells) Assembled in Malaysia (Module) Specifications included in this datasheet are subject to change without notice. ©2023 Maxeon Solar Technologies. All Rights Reserved. View warranty, patent and trademark information at maxeon.com/legal.

SUNPOWER

549398 REV A / A4_AU Publication Date: March 2023



Standard Tests ³

Available Listings

IFLI Declare Label

Silver

Contribution

EHS Compliance

Quality Management Certs

Cradle to Cradle Certified[™]

Green Building Certification

